



SATIN STAR

Dual Speed Wear Resistant Satin Sealer/Finish

DESCRIPTION

Satin Star has been formulated to give a satin finish to most surfaces with great wearability and chemical resistance.

DIRECTIONS FOR USE

(See How to Manual for details on most floor surfaces.)

Terrazzo, concrete, marble and other porous stone surfaces: Always pre-seal with Blockade or Bedrock for maximum adhesion and chemical resistance.

Commercial vinyl tiles: Pre-seal with Bedrock.

All other floor surfaces: No need to pre-seal, apply two to five coats, depending on depth of gloss preferred.

Dry/Recoat time: 15 – 45 mins (All depending on weather conditions).

Walk on (light foot traffic) : approximately 1 hour.

Replace furniture: approximately 8 hours.

Normally cures in 24 hours.

MAINTENANCE

Use either Supastar or Neutraclean as per label.

SCRUBBING/POLISHING

Use either Neutraclean or Shiner for maximum wearability.

FIRST AID

Skin: Remove contaminated clothing. Flush with fresh water.

Eyes: Flush eyes with water for 15 minutes while keeping eyelids open. Seek medical advice.

Inhalation: Remove patient to fresh air.

*High Technology Chemistry and Cleaning Systems for the Carpet Maintenance and Sanitation
Industries*

Wedina Holdings Pty. Ltd. A.B.N 65 002 373 319
48 Wentworth Street, Granville NSW 2142. Ph: (02) 8868 6888 Fax: (02) 9682 6855
PO BOX 142 Artarmon NSW 1570

Email: contact@research-products.com.au Web: www.research-products.com.au
C:\Data\Product Info Literature\Research Products\Hard Floors\Sealer Finishes\SATIN STAR.doc